

Latest Version: 6.0

Question: 1

Suppose the following query in a Simple XML dashboard returns a table including hyperlinks:

```
<search>
```

```
<query>index news sourcetype web_proxy | table sourcetype title link
```

```
</query>
```

```
</search>
```

Which of the following is a valid dynamic drilldown element to allow a user of the dashboard to visit the hyperlinks contained in the link field?

A. `<option name "link.openSearch.viewTarget">$row.link$</option>`

B. `<drilldown>`

```
<link target=" blank">$$row.link$$</link>
```

```
</drilldown>
```

C. `<drilldown>`

```
<link target="_blank">$row.link|n$</link>
```

```
</drilldown>
```

D. `<drilldown>`

```
<link target "_blank">http://localhost:8000/debug/refresh</link>
```

```
</drilldown>
```

Answer: A

Reference:

<https://docs.splunk.com/Documentation/Splunk/8.1.2/Viz/BuildandeditdashboardswithSimplifiedXML>

Question: 2

When updating a knowledge object via REST, which of the following are valid values for the sharing Access Control List property?

- A. App
- B. User
- C. Global
- D. Nobody

Answer: A

Reference: <https://docs.splunk.com/Documentation/Splunk/8.1.2/RESTUM/RESTusing>

Question: 3

Which of the following are ways to get a list of search jobs? (Select all that apply.)

- A. Access Activity > Jobs with Splunk Web.
- B. Use Splunk REST to query the /services/search/jobs endpoint.
- C. Use Splunk REST to query the /services/saved/searches endpoint.
- D. Use Splunk REST to query the /services/search/sid/results endpoint.

Answer: AB

Reference:
<https://docs.splunk.com/Documentation/Splunk/8.1.2/Search/SupervisejobswiththeJobspage>

Question: 4

Which of the following are benefits from using Simple XML Extensions? (Select all that apply.)

- A. Add custom layouts.
- B. Add custom graphics.
- C. Add custom behaviors.
- D. Limit Splunk license consumption based on host.

Answer: AC

Reference: <https://dev.splunk.com/enterprise/docs/developapps/visualizedata/usewebframework/modifydashboards/>

Question: 5

How can indexer acknowledgement be enabled for HTTP Event Collector (HEC)? (Select all that apply.)

- A. No need to do anything, it is turned on by default.
- B. When a REST request is sent to create a token, the property for indexer acknowledgement must be set to 1.
- C. When a new HEC token is created in Splunk Web, select the checkbox labeled "Enable indexer acknowledgement".
- D. When the Global Settings for HEC are updated in Splunk Web, select the checkbox labeled "Enable indexer acknowledgement".

Answer: CD

Reference: <https://docs.splunk.com/Documentation/Splunk/8.1.2/Data/UsetheHTTPEventCollector>