

---

# Version: 6.0

## Question: 1

Which type of automatic remediation can be performed by the PTA in case of a suspected credential theft security event?

- A. Password change
- B. Password reconciliation
- C. Session suspension
- D. Session termination

**Answer: A**

Reference: <https://docs.cyberark.com/Product-Doc/OnlineHelp/PAS/Latest/en/Content/PTA/Security-Configuration.htm>

## Question: 2

dbparm.ini is the main configuration file for the Vault.

- A. True
- B. False

**Answer: A**

Reference: <https://docs.cyberark.com/Product-Doc/OnlineHelp/PAS/Latest/en/Content/PASREF/DBParm.ini.htm>

## Question: 3

When working with the CyberArk High Availability Cluster, which services are running on the passive node?

- A. Cluster Vault Manager and PrivateArk Database
- B. Cluster Vault Manager, PrivateArk Database and Remote Control Agent
- C. Cluster Vault Manager
- D. Cluster Vault Manager and Remote Control Agent

---

**Answer: C**

Reference:  
Doc/OnlineHelp/PAS/Latest/en/Content/PASIMP/Managing-the-Server.htm

<https://docs.cyberark.com/Product-CyberArk-Digital-Cluster-Vault->

### Question: 4

When a DR Vault Server becomes an active vault, it will automatically revert back to DR mode once the Primary Vault comes back online.

- A. True, this is the default behavior.
- B. False, the Vault administrator must manually set the DR Vault to DR mode by setting "FailoverMode=no" in the padr.ini file.
- C. True, if the AllowFailback setting is set to "yes" in the padr.ini file.
- D. False, the Vault administrator must manually set the DR Vault to DR mode by setting "FailoverMode=no" in the dbparm.ini file.

**Answer: A**

Reference:  
Doc/OnlineHelp/PAS/11.3/en/Content/PASIMP/Initiating-DR- Failback-to-Production-Vault.htm

<https://docs.cyberark.com/Product->

### Question: 5

Which onboarding method is used to integrate CyberArk with the accounts provisioning process?

- A. Accounts Discovery
- B. Auto Detection
- C. Onboarding RestAPI functions
- D. PTA rules

**Answer: B**

Reference:  
Doc/OnlineHelp/PAS/Latest/en/Content/PASIMP/Provisioning- Accounts-Automatically.htm

<https://docs.cyberark.com/Product->

### Question: 6

Which file is used to open up a non-standard firewall port to the Vault?

- A. dbparm.ini

- 
- B. PARagent.ini
  - C. passparm.ini
  - D. Vault.ini

**Answer: A**