

Latest Version: 6.0

Question: 1

For TCP connections, when a packet arrives at the Firewall Kernel out of sequence or fragmented, which layer of IPS corrects this to allow for proper inspection?

- A. Passive Streaming Library
- B. Protections
- C. Protocol Parsers
- D. Context Management

Answer: D

Question: 2

What command is usually used for general firewall kernel debugging and what is the size of the buffer that is automatically enabled when using the command?

- A. fw ctl debug, buffer size is 1024 KB
- B. fw ell zdebug, buffer size is 32768 KB
- C. fw dl zdebug, buffer size is 1 MB
- D. fw ctl kdeoug, buffer size is 32000 KB

Answer: D

Question: 3

What does CMI stand for in relation to the Access Control Policy?

- A. Content Matching Infrastructure
- B. Content Management Interface
- C. Context Management Infrastructure
- D. Context Manipulation Interface

Answer: C

Question: 4

When a User process or program suddenly crashes, a core dump is often used to examine the problem. Which command is used to enable the core-dumping via GAIA dish?

- A. set core-dump enable
- B. set core-dump per_process
- C. set user-dump enable
- D. set core-dump total

Answer: A

Question: 5

PostgreSQL is a powerful, open source relational database management system Check Point offers a command for viewing the database to interact with Postgres interactive shell Which command do you need to enter the PostgreSQL interactive shell?

- A. psql_client cpm postgres
- B. mysql_client cpm postgres
- C. psql_c!ieni postgres cpm
- D. mysql -u root

Answer: A