

Latest Version: 13.0

Question: 1

Which three elements must be configured In Avaya Aura® Communication Manager to build an H.323 Trunk? (Choose three.)

- A. an ISDN Trunk Group
- B. an E1/T1 Trunk Group
- C. an H.323 Signaling Group
- D. a SIP Signaling Group, changing it to H.323 type afterwards
- E. a Name/IP-Address entry to the Node-Names IP table

Answer: AB, C

Question: 2

Which communication Manager Reset level takes less than 10 seconds, and preserves stable calls as well Error and Alarm logs?

- A. Reset System 4
- B. Reset System 3
- C. Reset System 2
- D. Reset System 1

Answer: A

Question: 3

Which three tests are part of Communication Manager's Background testing strategy? (Choose three.)

- A. Fixed-Interval
- B. System
- C. Periodic
- D. Triggered
- E. Scheduled

Answer: A, C, E

Question: 4

How many Class of Restriction (COR) profiles does Communication Manager 8.x have?

- A. 538
- B. 250
- C. 996
- D. 100

Answer: C

Question: 5

Which three Interfaces can be used to add, change, and remove a Communication Manager (CM) H.323 Endpoint? (Choose three.)

- A. Linux Command Line at CM Server.
- B. "Communication Manager" Administration menu at Avaya Aura® System Manager (SMGR).
- C. Avaya Site Administration Terminal Emulation.
- D. SMI Web-Interface at CM Server.
- E. SAT terminal via SSH-session (for example, Putty).

Answer: BCE

Question: 6

In Avaya Aura® Communication Manager, which three options correspond to common maintenance commands? (Choose three.)

- A. Status
- B. Release
- C. Shutdown now -r
- D. Busyout
- E. Remove Station

Answer: A,B,D

Question: 7

Communication Manager translation data will be saved under which two circumstances? (Choose two.)

- A. Automatically every day during CM's Scheduled Maintenance
- B. When the save translation command is run from the Communication Manager Command Line
- C. Automatically during a Communication Manager reboot/restart
- D. Automatically during System Manager synchronization
- E. Automatically after every SAT command

Answer: A, B

<https://downloads.avaya.com/css/P8/documents/100089289>

Question: 8

In Avaya Aura® Communication Manager (CM), to create new codes to activate/deactivate call forwarding, which SAT command must you use?

- A. new feature-code
- B. add feature call-forward
- C. change fac
- D. change feature-access-code

Answer: D

Question: 9

When adding an H.323 Station, which three fields must be administered? (Choose three.)

- A. Extension
- B. Port
- C. Set Template/Set Type
- D. Security Code
- E. Class of Service (COS)

Answer: A, C, D

Question: 10

You try to add a new station start Inn with the digit 7 that has never been used before. How do you enable stations to be built with this new range?

- A. Change dial plan parameters

- B. Add station-range7
- C. Change dial plan analysis
- D. Add dial plan analysis 7

Answer: C

Question: 11

How do calls access the ARS routing tables?

- A. By using the Toll Analysis table
- B. By using the Public Unknown Numbering table
- C. By using Dial Plan Parameters
- D. By using the Feature Access Code

Answer: A

Question: 12

Which list command can trace the traffic entering and leaving Communication Manager on a specific trunk?

- A. list trace vdn
- B. list trace tac
- C. list trace station
- D. list trace ras

Answer: B