

Question: 1

During an initial setup of a Synergy environment, an integrator needs to enable or disable authorized Service access.

What will be the outcome when the integrator disables this service?

- A. Authenticated administrators will be unable to make changes to the system
- B. Authorized users will be unable to generate a support dump
- C. Authenticated administrators will be unable to access the system
- D. Authorized support will be unable to diagnose the system

Answer: D

Reference:

https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-c05098314 (62)

Question: 2

A customer has the following configuration:

Frame 1

- Bay 1 – HPE Synergy 12Gb SAS Connection Module
- Bay 2
- Bay 3 – HPE Virtual Connect SE 40 GB F8 Module
- Bay 4 – HPE Synergy 12GB SAS Connection Module
- Bay 5
- Bay 6 – HPE Synergy 10 Gb Interconnect Link Module

Frame 2

- Bay 1 – HPE Synergy 12Gb SAS Connection Module
- Bay 2
- Bay 3 – HPE Synergy 10Gb Interconnect Link Module
- Bay 4 – HPE Synergy 12Gb SAS Connection Module
- Bay 5
- Bay 6 – HPE Virtual Connect SE 40Gb F8 Module

How many more frames can the customer add to their Synergy composable fabric? (Note: Enter your answer in the answer field below.)

A. Frame 1 – Bay 2 – HPE Virtual Connect SE 100Gb F32 Module for Synergy (867796-B21)

Frame 1 – Bay 5 – HPE Virtual Connect SE 16Gb Fibre Channel Module for Synergy (779227-B21)

Frame 2 - Bay 2 – Brocade 16Gb/24 Power Pack+ Fibre Channel SAN Switch Module for HPE Synergy (K2Q86A)

Frame 2 – Bay 5 – HPE Synergy 4820C 10/20/25Gb Converged Network Adapter (876449-B21)

B. Frame 1 – Bay 2 – HPE Virtual Connect SE 100Gb F32 Module for Synergy

(867796-B21)

Frame 1 – Bay 5 – HPE Virtual Connect SE 16Gb Fibre Channel Module for Synergy (779227-B21)

Frame 2 – Bay 5 – HPE Synergy 4820C 10/20/25Gb Converged Network Adapter (876449-B21)

Answer: A

Question: 3

In a 3-frame HPE Synergy environment, how should an integrator place the image Streamer modules to allow for redundancy to all of the management connections?

- A. one Image Streamer module in frame 2, and a second Image Streamer Module in frame 3 (2 total)
- B. two Image Streamer modules in frame 2, and two Image Streamer modules in frame 3 (4 total)
- C. one Image Streamer module in each Synergy frame (3 total)
- D. two Image Streamer modules in frame 1 (2 total)

Answer: B

Reference:

https://www.karma-group.ru/upload/iblock/2be/synergy_image_streamer.pdf (page 7)

Question: 4

HOTSPOT

An integrator has installed a new Synergy frame into a rack with two existing Synergy frames in a customer's environment.

Click where the integrator should verify that the cabling for the management ring was completed correctly.

0000A66101

General >
 State
 Model
 Logical enclosure

Utilization >
 Power
 Temperature

Hardware >
 Location
 Powered by
 Serial number

View

Overview

General
 Hardware
 Firmware
 Devices
 Interconnects
 Power Supplies
 Fans
 Composable Infrastructure Appliances
 Link Modules
 Power
 Utilization
 Interconnect Link Topology
 Frame Link Topology
 Remote Support

Actions ▾

View Devices Composable Infrastructure Appliances

Rear View Interconnects Fans Link Modules Power Supplies

Answer:

0000A66101

General >
 State
 Model
 Logical enclosure

Utilization >
 Power
 Temperature

Hardware >
 Location
 Powered by
 Serial number

View

Overview

General
 Hardware
 Firmware
 Devices
 Interconnects
 Power Supplies
 Fans
 Composable Infrastructure Appliances
 Link Modules
 Power
 Utilization
 Interconnect Link Topology
 Frame Link Topology
 Remote Support

Actions ▾

View Devices Composable Infrastructure Appliances

Rear View Interconnects Fans Link Modules Power Supplies

Reference:
https://support.hpe.com/hpsc/doc/public/display?docId=a00048164en_us

Question: 5

Refer to the exhibit.

Interconnect Bay



Rear of HPE Synergy Frame

How should an integrator pair interconnect bays to set up redundant fabrics in an HPE Synergy 12000 Frame?

- A. Interconnect bays 1 and 2; bays 3 and 4; bays 5 and 6.
- B. Interconnect bays 1 and 6; bays 2 and 5; bays 3 and 4.
- C. Interconnect bays 1 and 4; bays 2 and 5; bays 3 and 6.
- D. Interconnect bays 1 and 3; bays 2 and 4; bays 5 and 6.

Answer: C

Reference:

<https://h20195.www2.hpe.com/v2/GetPDF.aspx/c04815113.pdf>