

Question: 1

Which function key is used to start Safe Mode in Windows NT?

- A. F10
- B. F8
- C. F6
- D. Windows NT does not support Safe Mode

Answer:D

Question: 2

Which of the following environment variables overrides or extends the list of directories holding shared libraries?

- A. LD_LOAD_PATH
- B. LD_LIB_PATH
- C. LD_LIBRARY_PATH
- D. LD_SHARE_PATH
- E. LD_RUN_PATH

Answer:C

Question: 3

Which RPM command will output the name of the package which supplied the file /etc/exports?

- A. rpm -F /etc/exports
- B. rpm -qf /etc/exports
- C. rpm -Kl /etc/exports
- D. rpm -qp /etc/exports
- E. rpm -qi /etc/exports

Answer:B

Question: 4

When removing a package, which of the following dpkg options will completely remove the files including configuration files?

- A. --clean
- B. --delete
- C. --purge
- D. -remove

Answer:C

Question: 5

Which file should be edited to select the network locations from which Debian installation package files are loaded?

- A. /etc/dpkg/dpkg.cfg
- B. /etc/apt/apt.conf
- C. /etc/apt/apt.conf.d
- D. /etc/apt/sources.list
- E. /etc/dpkg/dselect.cfg

Answer:D

Question: 6

Which command will disable swapping on a device? (Specify ONLY the command without any path or parameters.)

Answer:swapoff, /s

bin/swapoff

Question: 7

Which Debian package management tool asks the configuration questions for a specific already installed package just as if the package were being installed for the first time? (Specify ONLY the command without any path or parameters.)

Answer:dpkg-reconf

figure

Question: 8

Which of the following commands overwrites the bootloader located on /dev/sda without overwriting the partition table or any data following it?

- A. dd if=/dev/zero of=/dev/sda bs=512
- B. dd if=/dev/zero of=/dev/sda bs=512 count=1
- C. dd if=/dev/zero of=/dev/sda bs=440 count=1
- D. dd if=/dev/zero of=/dev/sda bs=440

Answer:C

Question: 9

Which of the following commands can be used to create a USB storage media from a disk image?

- A. gdisk
- B. dd
- C. cc
- D. fdisk
- E. mount

Answer: B

Question: 10

In Bash, inserting 1>&2 after a command redirects

- A. standard error to standard input.
- B. standard input to standard error.
- C. standard output to standard error.
- D. standard error to standard output.
- E. standard output to standard input.

Answer: C

Question: 11

What command will generate a list of user names from /etc/passwd along with their login shell?

- A. column -s : 1,7 /etc/passwd
- B. chop -c 1,7 /etc/passwd
- C. colrm 1,7 /etc/passwd
- D. cut -d: -f1,7 /etc/passwd

Answer: D

Question: 12

In a nested directory structure, which find command line option would be used to restrict the command to searching down a particular number of subdirectories?

- A. -dirmax
- B. -maxdepth
- C. -maxlevels
- D. -n
- E. -s

Answer: B
