

Latest Version: 18.0

Question: 1

Which of the following TOGAF components was created to enable architects to design architectures addressing Boundary less Information Flow?

- A. The Architecture Repository
- B. The Enterprise Continuum
- C. The Integrated Information Infrastructure Model
- D. The TOGAF Technical Reference Model

Answer: C

Question: 2

Which of the following best describes the TOGAF Technical Reference Model?

- A. It is a detailed data model that can be tailored to specific industries
- B. It is an example of a Common Systems Architecture
- C. It is a fundamental architecture upon which more specific architectures can be based
- D. It is a model of application components and application services software, including brokering applications

Answer: C

Question: 3

Which one of the following statements about the structure of the TOGAF 9 document is true?

- A. Part I, the Enterprise Continuum, describes a model for structuring a virtual repository
- B. Part II, the Architecture Development Method, describes the definitions of terms used in TOGAF, and the changes between versions of TOGAF
- C. Part III, Tools and Support, describes a collection of guidelines and techniques used in the other parts of TOGAF
- D. Part VI, TOGAF Reference Models, includes a model for release management of the TOGAF specification
- E. Part VII, the Architecture Capability Framework, describes processes and skills to establish an enterprise function

Answer: E

Question: 4

Which phase of the ADM ensures that implementation projects conform to the defined architecture?

- A. Requirements Management
- B. Phase D
- C. Phase F
- D. Phase G
- E. Phase H

Answer: D

Question: 5

Complete the sentence. The Requirements Management Phase _____.

- A. addresses and resolves requirements between ADM phases
- B. is a central process that prioritizes requirements for all ADM phases
- C. is used to dispose of resolved requirements for all ADM phases
- D. generates new requirements and passes them to all ADM phases
- E. stores requirements and manages their flow into relevant ADM phases

Answer: E

Question: 6

Which one of the following is an objective of the Preliminary Phase of the ADM?

- A. To define the Baseline Architecture for this cycle of the ADM
- B. To define the application systems for the Target Architecture
- C. To define the framework and methodologies to be used
- D. To define the relevant stakeholders and their concerns
- E. To define and prioritize work packages

Answer: C

Question: 7

According to TOGAF, when creating views for a particular architecture, what is the recommended first

step?

- A. Design a viewpoint to address all stakeholder concerns
- B. Develop views for the target architecture first
- C. Ensure completeness of the architecture
- D. Refer to existing libraries of viewpoints, to identify one for re-use

Answer: D

Question: 8

Which of the following architectures in the Architecture Continuum contains the most re-usable architecture elements?

- A. Common Systems Architectures
- B. Foundation Architectures
- C. Industry Architectures
- D. Organization-Specific Architectures

Answer: B

Question: 9

Which of the following describes the Architecture Vision document?

- A. A description of individual change increments showing progression from the baseline to target architecture
- B. A detailed schedule for implementation of the target architecture
- C. A high level description of the baseline and target architectures
- D. A joint agreement between the development team and sponsor on the deliverables and quality of an architecture
- E. A set of rules and guidelines to support fulfilling the mission of the organization

Answer: C

Question: 10

According to TOGAF, which of the following best describes how the Enterprise Continuum is used in organizing and developing an architecture?

- A. It is used to coordinate with the other management frameworks in use
- B. It is used to describe how an architecture addresses stakeholder concerns

- C. It is used to identify and understand business requirements
- D. It is used to provide a system for continuous monitoring
- E. It is used to structure re-usable architecture and solution assets

Answer: E