

Latest Version: 6.0

Question: 1

What is the purpose of link adaptation?

Response:

- A. Establishes STA-to-STA communication
- B. Allows a Beamformer to estimate the channel in order to calculate a steering matrix
- C. Performs over-the-air calibration to reduce the differences between a STA's transmit and receive radio chains
- D. Dynamically assigns an MCS

Answer: D

Question: 2

You want to simplify viewing frames of a particular type in Wireshark. What is used to specify frames for colorization?

Response:

- A. Custom code must be written and the binaries recompiled
- B. Automated protocol analysis is used and no additional options may be specified
- C. Filters are used to define the frames that should be colorized
- D. A scripting language is available to modify the code before recompilation

Answer: C

Question: 3

How does a client station indicate that it is using Power Save mode?

Response:

- A. It transmits a frame to the access point with the Sleep field set to 1.
- B. It transmits a frame to the access point with the Power Management field set to 1.
- C. Using DTIM, the access point determines when the client station uses Power Save mode.
- D. It doesn't need to, because Power Save mode is the default.

Answer: B

Question: 4

Which of the following are protection mechanisms?
(Choose two.)

Response:

- A. NAV back-off
- B. RTS/CTS
- C. RTS-to-self
- D. CTS-to-self
- E. WEP encryption

Answer: BD

Question: 5

In RF monitor mode, how will a wireless network adapter operate?

Response:

- A. Can capture traffic from only the BSS to which it is associated
- B. Can capture traffic from all BSSs without affecting normal network operation
- C. Becomes a completely passive listening device, and normal network operation is disabled
- D. Uses time division multiplexing to split its time between listening and transmitting; network operation will be slower

Answer: C

Question: 6

What is the name of the element used by APs to order stations to stop sending signals?

Response:

- A. Quiet
- B. Deauthentication
- C. Power Save
- D. DELTS

Answer: A

Question: 7

Having the wrong country code configured could cause which of the following problems?

Response:

- A. The protocols decodes to be in the wrong language
- B. The wrong number of channels available
- C. The protocol analyzer software to crash
- D. Your access points to switch channels

Answer: B

Question: 8

The Transmit Beamforming Capabilities field is part of which information element?

Response:

- A. HT information element
- B. HT 20/40 BSS Coexistence element
- C. HT Operation element
- D. HT Capabilities element

Answer: D

Question: 9

You are tasked with describing the various frames used in 802.11 communications. What frame is used for spectrum management, fast BSS transition and some other actions taken within a BSA?

Response:

- A. BlockAck
- B. CTS
- C. PS Poll
- D. Action

Answer: B

Question: 10

In which frame would you find a timestamp field?

Response:

- A. Beacon

- B. Association request
- C. Association response
- D. Authentication

Answer: A