Latest Version: 6.0

lack	
Question:	
Questioni	

The level of learning and training offered by RP 577 is ______.

- A. consistent with an AWS CWI
- B. the same as required for an AWS CWI
- C. not a replacement for AWS CWI training
- D. automatically makes one a welding inspector

Answer: C

Question: 2

DCEN means.

- A. direct current, electrode none
- B. direct current, electrode negative
- C. don't come easy, Norman
- D. direct current, electrode normal

Answer: B

Question: 3

Another name or abbreviation for a penetrameter is:

A. O.C.T.

B. D.E.Q.

C. I.Q.I.

D. D.T.Q.

Answer: C

Question: 4

A theoretical throat dimension is based on the assumption that the root opening is equal to:

A. zero B. 1/16 C. 1/8 D. 1/32 - 1/16 **Answer: A Question: 5** Welding inspection is a critical part of any _____ program. A. Quality Assurance **B.** Quality Process C. ISO 9000 D. ISO 11000 **Answer: A** Question: 6 Welding inspection can be separated into 3 distinct stages: A. welding, NDE, hardness testing B. pre-welding, NDE, heat treatment C. visual, NDE, RT D. before welding, during welding, after welding **Answer: D Question: 7** One of the items that should be checked prior to welding is:

A. confirm NDE examiners qualifications

B. confirm acceptability of heat treatment procedures

C. review WPS, PQR, and WPQ's

D. All of the above should be checked prior to welding

Answer: D

Question: 8

- A. removed and re-inspected
- B. radiographed to determine extent
- C. shearwave tested
- D. evaluated to API 580 acceptance criteria

Answer: A

Question: 9

NDE examiners should be qualified to _____ when specified by the referencing code.

- A. ASME XII
- B. API 570
- C. SNT-TC-1A
- D. API 510

Answer: C

Question: 10

As a minimum, each Inspector should review the _____ prior to starting each job.

- A. OSHA regulations
- B. EPA regulations
- C. site safety rules
- D. HAZWOPER Guidelines

Answer: C

Question: 11

An advantage of SMAW is:

- A. equipment is very expensive
- B. slag must be removed from weld passes
- C. can be used on almost all commonly-used metal or alloy

D. deposition rates are much higher than for other processes

Answer: C

Question: 12

GTAW and SMAW can be distinguished from other processes as they are both used with _____.

- A. cc power supplies
- B. cv power supplies
- C. external gas shielding
- D. flux cored electrodes

Answer: A